

## SoliTek PRIME framed 240 - 250

Glass/Glass polycrystalline 60 cell module

Glass/Glass modules – advanced choice for those who look for durability, safety, efficiency.

### KEY FEATURES



**30+ year lifetime.** Edge-sealant protection assures superior atmospheric and humidity resistance.



**Back glass** instead of plastic assures durability and robust protection against UV, moisture, ammonia and salt corrosion.



**Higher heat dispensing.** Glass is better thermal conductor than plastic back-sheet in standard modules ensuring higher efficiency in hot climate.



**100% PID free cells.** Potential induced degradation is eliminated at cell level using PVB lamination foil.



Compliant with IEC 61215:2005, IEC 61730:2004 standard



**Wider light spectrum absorbed.** PVB lamination foil utilise light spectrum starting from 280nm.

### LAMINATION FOIL:



Black

White

Transparent

### Why Glass/Glass technology?

Glass/Glass (G/G) modules are produced by laminating PV cells between two glasses, instead of standard glass and plastic.

In comparison with standard modules, the same glass material resistance and heat dispensing is more durable in fluctuating temperatures, hot and humid climate zones, ensuring 30-40 years lifetime.

Unlike other G/G modules in the market, SoliTek uses innovative edge-sealant technology to protect PV cells from humidity.

PV cells are manufactured in-house using advanced technologies ensuring elimination of potential induced degradation (100% PID free cells).


Both SoliTek cells and modules are manufactured using green energy – geothermal, solar and hydro power.

### RELIABLE QUALITY

- Positive power tolerance 0-3%
- 100% double sorting ensures modules are defect free
- Fully automated production lines eliminates human mistakes
- Manufactured and assembled in EU (Vilnius, Lithuania)

### MANUFACTURER WARRANTY

- 20 years product warranty
- 30 years performance warranty at 80% output
- 2 years all risk insurance. Available for the following countries: Germany, Austria, Switzerland, Liechtenstein, Luxemburg, UK, France and North Italy



Certified by



IEC 61215:2005  
IEC 61730:2004 standard



### MECHANICAL PARAMETERS

Cell (mm)	Poly 156x156
Weight (kg)	23.5 (approx)
Dimensions (LxWxH) (mm)	1682 x 1000 x 41
Cable Cross Section Size (mm <sup>2</sup> ) / Plugs	4 / MC4 compatible
No. of Cells in the Line	60 (10x6)
Junction Box	Huber+ Suhner J-Box
Front / Back Glass (mm)	2,1 / 2,1
Packaging Configuration	16 per pallet





### WORKING CONDITIONS

Maximum System Voltage	DC 1000V (TÜV)
Operating Temperature	-40 °C~+85°C
Maximum Reverse Current	15A
Maximum Static Load, Front (wind / snow)	2400Pa / 5400Pa
NOCT	43,6 °C
Application Class	Class A

### ELECTRICAL PARAMETERS

TYPE	SoliTek PRIME framed 240 - 250	SoliTek PRIME framed 240 - 250	SoliTek PRIME framed 240 - 250
Rated Maximum Power at STC (Wp)	240	245	250
Open Circuit Voltage (Voc/V)	37.82	37.80	37.90
Maximum Power Voltage (Vmp/V)	30.54	30.85	30.70
Short Circuit Current (Isc/A)	8.41	8.58	8.60
Maximum Power Current (Imp/A)	7.85	7.94	8.10
Module Efficiency [%]	14.50	14.80	15.08
Power Tolerance	0+3%	0+3%	0+3%
Temperature Coefficient of Isc (αIsc)	+0.05%/°C	+0.05%/°C	+0.05%/°C
Temperature Coefficient of Voc (βVoc)	-0.34%/°C	-0.34%/°C	-0.34%/°C
Temperature Coefficient of Pmax (γPmp)	-0.42%/°C	-0.42%/°C	-0.42%/°C
STC	Irradiance 1000W/m <sup>2</sup> , Module Temperature 25°C, AM 1.5		

### I-V CURVE



Note:  
Dimensions are given in millimeters

Specifications subject to technical changes and tests. Manufacturer reserves the right of final interpretation.